

# QD600 Digital Visual Presenter



- XGA Output with 16 x Optical Zoom and 8 x Digital Zoom
- USB port for Video record and image save/edit/recall on both PC and Mac
- 2 RGB Inputs and 2 RGB outputs provide outstanding visual presentation possibilities
- LED lights are cool to the touch and last up to 10 years
- Switch from Static mode to Dynamic mode to view still and moving images
- View transparencies, X-rays, photographic negatives, and microscope slides using the built in light box
- Split screen presents frame capture and live display side by side
- Create titles using title capture feature

**QOMO QD600**

## QD600 Digital Visual Presenter

|  |   |
|--|---|
| <b>Color System</b>                    | NTSC or PAL system  |
| <b>Pickup Device</b>                   | 1/4" Professional CCD   |
| <b>XGA Output Pixels</b>               | 780,000   |
| <b>Powered Room</b>                    | 16x Optical and 8x Digital  |
| <b>Lens</b>                            | F=1.6~3.7mm / f=3.9~85.8 mm   |
| <b>Focus/Iris</b>                      | Auto/Manual Selectable  |
| <b>White Balance</b>                   | Auto  |
| <b>Image Split</b>                     | Yes   |
| <b>Negative/Positive Conversion</b>    | Yes   |
| <b>Black/White and Color Selection</b> | Yes   |
| <b>Image Freeze</b>                    | Yes   |
| <b>Mirror</b>                          | Yes   |
| <b>Lights</b>                          | Arm Light: 1.5 W LED Lamps × 2<br>Back Light: 4 W LED Lamps   |
| <b>Input Connectors</b>                | MIC: Mini Jack × 1<br>PC Audio: Mini Jack × 2<br>RGB: 15 Pin 'D' Connector × 2  |
| <b>Output Connectors</b>               | RGB: 15 Pin 'D' Connector × 2<br>C–Video: RCA Jack × 1<br>S–Video: 4 Pin Mini Din × 1<br>Audio: Mini Jack × 1   |
| <b>Operating System</b>                | Windows 2000/XP   |
| <b>USB Connector</b>                   | 30 Frames/Sec   |
| <b>RS–232 Connector</b>                | 9–pin, D–Sub, Male/6–Pin PS/2   |
| <b>USB Port</b>                        | USB 2.0   |
| <b>Power Requirements</b>              | 12V/4A External AC Adapter  |
| <b>Dimension (W x D x H)</b>           | Folded: 20.0 " × 16.1 " × 4.7 " (50.8cm × 20.9cm × 11.9cm)<br>Setup: 20.0 " × 20.9 " × 22.4 " (50.8cm × 53.1cm × 56.9cm)<br>Packing: 25.6 " × 21.3 " × 9.1 " (65cm × 54.1cm × 23.1cm)   |
| <b>Weight</b>                          | N.W: 12.1lbs (5.5Kg)<br>G.W: 20.9 lbs (9.5Kg)   |
| <b>Accessories</b>                     | AC Power Cord<br>RGB Cable<br>Audio/Video Cable<br>S–Video Cable<br>Computer RS232 Cable (9–Pin to 9–Pin)<br>USB Cable<br>Audio Convert Cable<br>AC Adapter<br>User's Manual<br>Quick Start–up Guide<br>Software CD<br>Infrared Remote Control<br>Warranty Card |

\* Design and specifications are subject to change without notice.

